

texdoc 2.0
An update on creating LaTeX documents from within Stata

Example 2

Ben Jann
University of Bern, ben.jann@soz.unibe.ch

UK Stata Users Group meeting
London, September 89, 2016

Contents

1	The texdoc source file	2
2	The resulting \LaTeX source file	6
3	The resulting PDF	8

1 The texdoc source file

— *crosswise09.texdoc* —

```
texdoc init crosswise09, replace logdir logall

/**
\documentclass{article}
\usepackage{stata}
\usepackage{graphicx, hyperref}

\title{My Analysis of the Crosswise09 Data}
\author{Ben Jann}
\date{\today}

\begin{document}

\maketitle

\tableofcontents

\section{Settings}

***/

about
version 14.1
clear all
set linesize 100
set type double
set more off
// required user packages: fre, rrreg, rrlogit, estout, coefplot

/**

\section{Number of Observations}

***/

use crosswise09.dta
fre uni
fre version
fre f7
tab uni version, chi2 exact
gen byte touse = (f7!=1) | inlist(b1,1,2) | inlist(b2,1,2) ///
                  | inlist(f11,1,2) | inlist(f12,1,2)

fre touse
fre version if touse
tab uni version if touse, chi2 exact

/**
```

```
\section{Item-Nonresponse}
```

```
***/
```

```
gen byte partial    = b1==1 if inlist(b1,1,2) & version==1 & touse
gen byte severe     = b2==1 if inlist(b2,1,2) & version==1 & touse
replace partial     = f11==1 if inlist(f11,1,2) & version==2 & touse
replace severe      = f12==1 if inlist(f12,1,2) & version==2 & touse
gen byte missing = (partial>=.)
tab version missing if touse, missing row
drop missing
gen byte missing = (severe>=.)
tab version missing if touse, missing row
drop missing
gen byte missing = (partial>=.) | (severe>=.)
tab version missing if touse, missing row
drop missing
count if (partial<.) & (severe>=.) & touse
count if (partial>=.) & (severe<.) & touse
```

```
/***
```

```
\section{Table 1: Descriptives}
```

```
***/
```

```
su f2 if touse
egen byte agecat = cut(f2) if touse, at(18,23,28,`r(max)')
tab agecat version if touse, chi2 exact col
tab f1 version if touse, chi2 exact col
tab f3 version if touse, chi2 exact col
```

```
/***
```

```
\section{Table 2: Prevalence estimates}
```

```
***/
```

```
gen byte crosswise = version==1 if touse
gen pyes           = cond(crosswise, 0.25, 1) if touse
```

```
// - direct questioning (DQ)
```

```
reg partial if crosswise==0
reg severe  if crosswise==0
```

```
// - crosswise model (CM)
```

```
rrreg partial if crosswise, pw(pyes)
rrreg severe  if crosswise, pw(pyes)
```

```

// - difference between DQ and CM

rrreg partial crosswise, pw(pyes) robust hc2
rrreg severe crosswise, pw(pyes) robust hc2

/****

\section{Table 3: Regression estimates}

****/

gen byte female      = f1==2 if inlist(f1,1,2)
gen byte internet    = f8_4==1
gen byte students    = f8_5==1
gen byte papers3or4  = f7==3 if f7<.
gen byte papers5     = f7==4 if f7<.
gen byte zurich      = uni==1
gen byte munich      = uni==2

su partial crosswise zurich munich female ///
    papers3or4 papers5 internet students if partial<.
su partial crosswise zurich munich female ///
    papers3or4 papers5 internet students if partial<. & crosswise==1

eststo reg1: rrreg partial ///
    zurich munich ///
    female papers3or4 papers5 internet students ///
    if crosswise, pw(pyes) robust
test zurich = munich

eststo logit1: rrlogit partial ///
    zurich munich ///
    female papers3or4 papers5 internet students ///
    if crosswise, pw(pyes) robust
test zurich = munich

eststo reg2: rrreg partial crosswise ///
    zurich munich ///
    female papers3or4 papers5 internet students ///
    , pw(pyes) robust
test zurich = munich

eststo logit2: rrlogit partial crosswise ///
    zurich munich ///
    female papers3or4 papers5 internet students ///
    , pw(pyes) nolog robust
test zurich = munich

esttab reg1 reg2 logit1 logit2, order(crosswise) ///
    compress mtitle nonumber star(+ 0.1 * 0.05 ** 0.01 *** 0.001)

```

```

/***

\section{Graph: Regression estimates}

***/

coefplot reg2 reg1 || logit2 logit1, drop(_cons) xline(0) ///
    bylabels(LPM Logit) byopts(xrescale legend(off))
texdoc graph

/***

\end{document}

— end of file —

```

2 The resulting L^AT_EX source file

Applying

```
. texdoc do crosswise09.texdoc
```

generates to the following L^AT_EX file.

— *crosswise09.tex* —

```
\documentclass{article}
\usepackage{stata}
\usepackage{graphicx, hyperref}

\title{My Analysis of the Crosswise09 Data}
\author{Ben Jann}
\date{\today}

\begin{document}

\maketitle

\tableofcontents

\section{Settings}

\begin{stlog}\input{crosswise09/1.log.tex}\end{stlog}

\section{Number of Observations}

\begin{stlog}\input{crosswise09/2.log.tex}\end{stlog}

\section{Item-Nonresponse}

\begin{stlog}\input{crosswise09/3.log.tex}\end{stlog}

\section{Table 1: Descriptives}

\begin{stlog}\input{crosswise09/4.log.tex}\end{stlog}

\section{Table 2: Prevalence estimates}

\begin{stlog}\input{crosswise09/5.log.tex}\end{stlog}

\section{Table 3: Regression estimates}

\begin{stlog}\input{crosswise09/6.log.tex}\end{stlog}

\section{Graph: Regression estimates}

\begin{stlog}\input{crosswise09/7.log.tex}\end{stlog}
\begin{center}
\includegraphics{crosswise09/7}
```

`\end{center}`

`\end{document}`

— end of file —

3 The resulting PDF

The following pages display the resulting PDF after compiling the \LaTeX source file.

My Analysis of the Crosswise09 Data

Ben Jann

September 8, 2016

Contents

1	Settings	1
2	Number of Observations	2
3	Item-Nonresponse	3
4	Table 1: Descriptives	5
5	Table 2: Prevalence estimates	6
6	Table 3: Regression estimates	8
7	Graph: Regression estimates	12

1 Settings

```
. about
Stata/MP 14.1 for Mac (64-bit Intel)
Revision 20 Jul 2016
Copyright 1985-2015 StataCorp LP
Total physical memory:      8.01 GB
30-user 2-core Stata network perpetual license:
    Serial number: 501406208640
    Licensed to: Ben Jann
                University of Bern

. version 14.1
. clear all
. set linesize 100
. set type double
. set more off
. // required user packages: fre, rrreg, rrlogit, estout, coefplot
```

2 Number of Observations

```
. use crosswise09.dta
```

```
. fre uni
```

```
uni — location of data collection
```

		Freq.	Percent	Valid	Cum.
Valid	1 ETH Zurich	111	23.42	23.42	23.42
	2 LMU Munich	90	18.99	18.99	42.41
	3 University Leipzig	273	57.59	57.59	100.00
	Total	474	100.00	100.00	

```
. fre version
```

```
version — experimental condition
```

		Freq.	Percent	Valid	Cum.
Valid	1 crosswise	358	75.53	75.53	75.53
	2 direct	116	24.47	24.47	100.00
	Total	474	100.00	100.00	

```
. fre f7
```

```
f7 — number of papers
```

		Freq.	Percent	Valid	Cum.
Valid	1 none	65	13.71	13.74	13.74
	2 one or two	178	37.55	37.63	51.37
	3 three or four	111	23.42	23.47	74.84
	4 five or more	119	25.11	25.16	100.00
	Total	473	99.79	100.00	
Missing	.	1	0.21		
Total		474	100.00		

```
. tab uni version, chi2 exact
```

```
Enumerating sample-space combinations:
```

```
stage 3: enumerations = 1
```

```
stage 2: enumerations = 2
```

```
stage 1: enumerations = 0
```

location of data collection	experimental condition		Total
	crosswise	direct	
ETH Zurich	85	26	111
LMU Munich	68	22	90
University Leipzig	205	68	273
Total	358	116	474

```
Pearson chi2(2) = 0.0942 Pr = 0.954
```

```
Fisher's exact = 0.967
```

```
. gen byte touse = (f7!=1) | inlist(b1,1,2) | inlist(b2,1,2) ///
> | inlist(f11,1,2) | inlist(f12,1,2)
```

```
. fre touse
```

```
touse
```

		Freq.	Percent	Valid	Cum.
Valid	0	64	13.50	13.50	13.50
	1	410	86.50	86.50	100.00
	Total	474	100.00	100.00	

```
. fre version if touse
version — experimental condition
```

		Freq.	Percent	Valid	Cum.
Valid	1 crosswise	313	76.34	76.34	76.34
	2 direct	97	23.66	23.66	100.00
	Total	410	100.00	100.00	

```
. tab uni version if touse, chi2 exact
```

Enumerating sample-space combinations:

stage 3: enumerations = 1

stage 2: enumerations = 1

stage 1: enumerations = 0

location of data collection	experimental condition		Total
	crosswise	direct	
ETH Zurich	55	16	71
LMU Munich	66	21	87
University Leipzig	192	60	252
Total	313	97	410

Pearson chi2(2) = 0.0639 Pr = 0.969
Fisher's exact = 0.972

3 Item-Nonresponse

```
. gen byte partial = b1==1 if inlist(b1,1,2) & version==1 & touse
(164 missing values generated)
. gen byte severe = b2==1 if inlist(b2,1,2) & version==1 & touse
(164 missing values generated)
. replace partial = f11==1 if inlist(f11,1,2) & version==2 & touse
(96 real changes made)
. replace severe = f12==1 if inlist(f12,1,2) & version==2 & touse
(96 real changes made)
. gen byte missing = (partial>=.)
. tab version missing if touse, missing row
```

Key
<i>frequency</i>
<i>row percentage</i>

```
experiment |
al         | missing
```

condition	0	1	Total
crosswise	310 99.04	3 0.96	313 100.00
direct	96 98.97	1 1.03	97 100.00
Total	406 99.02	4 0.98	410 100.00

```
. drop missing
. gen byte missing = (severe>=.)
. tab version missing if touse, missing row
```

Key
<i>frequency</i> <i>row percentage</i>

experimental condition	missing 0	1	Total
crosswise	310 99.04	3 0.96	313 100.00
direct	96 98.97	1 1.03	97 100.00
Total	406 99.02	4 0.98	410 100.00

```
. drop missing
. gen byte missing = (partial>=.) | (severe>=.)
. tab version missing if touse, missing row
```

Key
<i>frequency</i> <i>row percentage</i>

experimental condition	missing 0	1	Total
crosswise	309 98.72	4 1.28	313 100.00
direct	96 98.97	1 1.03	97 100.00
Total	405 98.78	5 1.22	410 100.00

```
. drop missing
. count if (partial<.) & (severe>=.) & touse
1
```

```
. count if (partial>=.) & (severe<.) & touse
1
```

4 Table 1: Descriptives

```
. su f2 if touse
Variable | Obs Mean Std. Dev. Min Max
-----+-----
f2 | 407 23.24324 3.799442 18 60
. egen byte agecat = cut(f2) if touse, at(18,23,28,`r(max)`)
(68 missing values generated)
. tab agecat version if touse, chi2 exact col
```

Key
<i>frequency</i>
<i>column percentage</i>

```
Enumerating sample-space combinations:
stage 3: enumerations = 1
stage 2: enumerations = 6
stage 1: enumerations = 0
```

agecat	experimental condition		Total
	crosswise	direct	
18	154 49.52	47 49.47	201 49.51
23	126 40.51	42 44.21	168 41.38
28	31 9.97	6 6.32	37 9.11
Total	311 100.00	95 100.00	406 100.00

```
Pearson chi2(2) = 1.3053 Pr = 0.521
Fisher's exact = 0.557
```

```
. tab f1 version if touse, chi2 exact col
```

Key
<i>frequency</i>
<i>column percentage</i>

sex	experimental condition		Total
	crosswise	direct	
male	154 49.68	42 43.30	196 48.16
female	156	55	211

	50.32	56.70	51.84
Total	310	97	407
	100.00	100.00	100.00

Pearson chi2(1) = 1.2040 Pr = 0.273
 Fisher's exact = 0.296
 1-sided Fisher's exact = 0.163
 . tab f3 version if touse, chi2 exact col

Key
<i>frequency</i>
<i>column percentage</i>

nationality	experimental condition		Total
	crosswise	direct	
german or swiss	288	93	381
	92.90	95.88	93.61
other	22	4	26
	7.10	4.12	6.39
Total	310	97	407
	100.00	100.00	100.00

Pearson chi2(1) = 1.0920 Pr = 0.296
 Fisher's exact = 0.351
 1-sided Fisher's exact = 0.214

5 Table 2: Prevalence estimates

```

. gen byte crosswise = version==1 if touse
(64 missing values generated)
. gen pyes = cond(crosswise, 0.25, 1) if touse
(64 missing values generated)
.
. // - direct questioning (DQ)
.
. reg partial if crosswise==0

```

Source	SS	df	MS	Number of obs	=	96
Model	0	0	.	F(0, 95)	=	0.00
Residual	6.48958333	95	.068311404	Prob > F	=	.
				R-squared	=	0.0000
				Adj R-squared	=	0.0000
Total	6.48958333	95	.068311404	Root MSE	=	.26136

partial	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
_cons	.0729167	.0266754	2.73	0.007	.0199593	.125874

```

. reg severe if crosswise==0

```

Source	SS	df	MS	Number of obs	=	96
				F(0, 95)	=	0.00

Model	0	0	.	Prob > F	=	.
Residual	.989583333	95	.010416667	R-squared	=	0.0000
				Adj R-squared	=	0.0000
Total	.989583333	95	.010416667	Root MSE	=	.10206

severe	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
_cons	.0104167	.0104167	1.00	0.320	-.010263	.0310964

```
.
. // - crosswise model (CM)
.
. rrreg partial if crosswise, pw(pyes)
Randomized response regression
```

Number of obs	=	310
F(0, 309)	=	0.00
Prob > F	=	.
R-squared	=	0.0000
Adj R-squared	=	0.0000
Root MSE	=	0.9623

partial	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
_cons	.2225806	.0546551	4.07	0.000	.1150374	.3301239

```
Pr(non-negated question) = pyes
Pr(surrogate "yes")      = 0
Pr(surrogate "no")       = 0
. rrreg severe if crosswise, pw(pyes)
Randomized response regression
```

Number of obs	=	310
F(0, 309)	=	0.00
Prob > F	=	.
R-squared	=	0.0000
Adj R-squared	=	0.0000
Root MSE	=	0.8766

severe	Coef.	Std. Err.	t	P> t	[95% Conf. Interval]	
_cons	.016129	.0497849	0.32	0.746	-.0818313	.1140894

```
Pr(non-negated question) = pyes
Pr(surrogate "yes")      = 0
Pr(surrogate "no")       = 0
.
. // - difference between DQ and CM
.
. rrreg partial crosswise, pw(pyes) robust hc2
Randomized response regression
```

Number of obs	=	406
F(1, 404)	=	6.05
Prob > F	=	0.0143
R-squared	=	0.0056
Adj R-squared	=	0.0031
Root MSE	=	0.8511

partial	Coef.	Robust Std. Err.	t	P> t	[95% Conf. Interval]	
crosswise	.149664	.0608271	2.46	0.014	.0300868	.2692411

	_cons	.0729167	.0266017	2.74	0.006	.0206216	.1252117
Pr(non-negated question) = pyes							
Pr(surrogate "yes") = 0							
Pr(surrogate "no") = 0							
. rrreg severe crosswise, pw(pyes) robust hc2							
Randomized response regression							
						Number of obs = 406	
						F(1, 404) = 0.01	
						Prob > F = 0.9107	
						R-squared = 0.0000	
						Adj R-squared = -0.0025	
						Root MSE = 0.7682	

	severe	Coef.	Robust Std. Err.	t	P> t	[95% Conf. Interval]
crosswise		.0057124	.0508988	0.11	0.911	-.0943471 .1057719
_cons		.0104167	.0103879	1.00	0.317	-.0100044 .0308377


```

Pr(non-negated question) = pyes
Pr(surrogate "yes") = 0
Pr(surrogate "no") = 0

```

6 Table 3: Regression estimates

```

. gen byte female = f1==2 if inlist(f1,1,2)
(3 missing values generated)
. gen byte internet = f8_4==1
. gen byte students = f8_5==1
. gen byte papers3or4 = f7==3 if f7<.
(1 missing value generated)
. gen byte papers5 = f7==4 if f7<.
(1 missing value generated)
. gen byte zurich = uni==1
. gen byte munich = uni==2
.
. su partial crosswise zurich munich female ///
> papers3or4 papers5 internet students if partial<.

```

Variable	Obs	Mean	Std. Dev.	Min	Max
partial	406	.5049261	.5005926	0	1
crosswise	406	.7635468	.4254279	0	1
zurich	406	.1724138	.3782058	0	1
munich	406	.2093596	.4073535	0	1
female	403	.5186104	.5002746	0	1
papers3or4	405	.2691358	.4440592	0	1
papers5	405	.2888889	.4538068	0	1
internet	406	.8940887	.3081038	0	1
students	406	.2413793	.4284478	0	1

```

. su partial crosswise zurich munich female ///
> papers3or4 papers5 internet students if partial<. & crosswise==1

```


Variable	Obs	Mean	Std. Dev.	Min	Max
partial	310	.6387097	.4811511	0	1
crosswise	310	1	0	1	1
zurich	310	.1741935	.3798891	0	1
munich	310	.2096774	.4077365	0	1
female	307	.504886	.5007924	0	1
papers3or4	309	.2944984	.4565563	0	1
papers5	309	.2912621	.455081	0	1
internet	310	.883871	.3208976	0	1
students	310	.2290323	.4208894	0	1

```
.
. eststo reg1: rrreg partial ///
>   zurich munich ///
>   female papers3or4 papers5 internet students ///
>   if crosswise, pw(pyes) robust
```

```
Randomized response regression      Number of obs   =      306
                                   F(   7,   298)   =      1.23
                                   Prob > F       =      0.2841
                                   R-squared        =      0.0258
                                   Adj R-squared    =      0.0029
                                   Root MSE      =      0.9599
```

partial	Coef.	Robust Std. Err.	t	P> t	[95% Conf. Interval]	
zurich	.1297747	.1679073	0.77	0.440	-.2006596	.4602089
munich	-.2022313	.1352413	-1.50	0.136	-.4683803	.0639178
female	.0313942	.1168534	0.27	0.788	-.1985681	.2613565
papers3or4	-.1129604	.1359154	-0.83	0.407	-.380436	.1545152
papers5	.0879665	.1432817	0.61	0.540	-.1940055	.3699386
internet	.1726924	.1687123	1.02	0.307	-.1593261	.5047109
students	.1897438	.1378786	1.38	0.170	-.0815952	.4610829
_cons	.0344005	.1662536	0.21	0.836	-.2927793	.3615803

```
Pr(non-negated question) = pyes
Pr(surrogate "yes")      = 0
Pr(surrogate "no")       = 0
```

```
. test zurich = munich
( 1)  zurich - munich = 0
      F(   1,   298) =    2.97
      Prob > F =    0.0860
```

```
.
. eststo logit1: rrlogit partial ///
>   zurich munich ///
>   female papers3or4 papers5 internet students ///
>   if crosswise, pw(pyes) robust
```

Fitting constant-only model:

```
Iteration 0:  log pseudolikelihood = -212.10304
Iteration 1:  log pseudolikelihood = -199.85397
Iteration 2:  log pseudolikelihood = -199.85373
Iteration 3:  log pseudolikelihood = -199.85373
```

Fitting full model:

```
Iteration 0:  log pseudolikelihood = -199.85373
Iteration 1:  log pseudolikelihood = -198.77043
Iteration 2:  log pseudolikelihood = -197.73043
```

Iteration 3: log pseudolikelihood = -196.81341
 Iteration 4: log pseudolikelihood = -196.68131
 Iteration 5: log pseudolikelihood = -196.68051
 Iteration 6: log pseudolikelihood = -196.68051

Randomized response logistic regression Number of obs = 306
 Nonzero outcomes = 196
 P(non-negated question) = pyes Zero outcomes = 110
 P(surrogate "yes") = 0 Wald chi2(7) = 6.36
 P(surrogate "no") = 0 Prob > chi2 = 0.4987
 Log pseudolikelihood = -196.68051 Pseudo R2 = 0.0159

partial	Coef.	Robust Std. Err.	z	P> z	[95% Conf. Interval]	
zurich	.5216706	.9830921	0.53	0.596	-1.405155	2.448496
munich	-1.001754	.9174338	-1.09	0.275	-2.799891	.7963832
female	.2318339	.8098296	0.29	0.775	-1.355403	1.819071
papers3or4	-.6753206	.8620195	-0.78	0.433	-2.364848	1.014207
papers5	.2226108	.8264936	0.27	0.788	-1.397287	1.842509
internet	1.011847	1.588698	0.64	0.524	-2.101945	4.125639
students	.9554459	.7934316	1.20	0.229	-.5996515	2.510543
_cons	-2.303029	1.297016	-1.78	0.076	-4.845134	.2390766

```
. test zurich = munich
( 1) [partial]zurich - [partial]munich = 0
      chi2( 1) =      1.64
      Prob > chi2 =      0.2001
.
. eststo reg2: rrreg partial crosswise ///
>   zurich munich ///
>   female papers3or4 papers5 internet students ///
>   , pw(pyes) robust
```

Randomized response regression Number of obs = 402
 F(8, 393) = 1.70
 Prob > F = 0.0976
 R-squared = 0.0268
 Adj R-squared = 0.0070
 Root MSE = 0.8472

partial	Coef.	Robust Std. Err.	t	P> t	[95% Conf. Interval]	
crosswise	.1722132	.0640163	2.69	0.007	.046356	.2980703
zurich	.122656	.1280605	0.96	0.339	-.1291133	.3744253
munich	-.1326625	.1057303	-1.25	0.210	-.3405302	.0752052
female	.0409437	.0889149	0.46	0.645	-.1338647	.2157522
papers3or4	-.097614	.1074576	-0.91	0.364	-.3088777	.1136497
papers5	.0471034	.109144	0.43	0.666	-.1674756	.2616825
internet	.1475172	.1376815	1.07	0.285	-.1231672	.4182016
students	.1606791	.1024078	1.57	0.117	-.0406565	.3620148
_cons	-.1198158	.1376898	-0.87	0.385	-.3905164	.1508849

```
Pr(non-negated question) = pyes
Pr(surrogate "yes")      =      0
Pr(surrogate "no")      =      0
. test zurich = munich
( 1) zurich - munich = 0
```

```

F( 1, 393) = 2.83
Prob > F = 0.0935
.
. eststo logit2: rrlogit partial crosswise ///
> zurich munich ///
> female papers3or4 papers5 internet students ///
> , pw(pyes) nolog robust
Randomized response logistic regression      Number of obs      =      402
Nonzero outcomes =      203
P(non-negated question) = pyes      Zero outcomes      =      199
P(surrogate "yes")      = 0      Wald chi2(8)      =      15.36
P(surrogate "no")      = 0      Prob > chi2      =      0.0526
Log pseudolikelihood = -220.02124      Pseudo R2      =      0.0339

```

partial	Coef.	Robust Std. Err.	z	P> z	[95% Conf. Interval]	
crosswise	1.640846	.5820506	2.82	0.005	.5000476	2.781644
zurich	.7572907	.7581485	1.00	0.318	-.7286531	2.243234
munich	-.2324246	.7642652	-0.30	0.761	-1.730357	1.265508
female	.5202687	.5969944	0.87	0.383	-.6498187	1.690356
papers3or4	-.7994094	.7180947	-1.11	0.266	-2.206849	.6080304
papers5	-.3420689	.7012229	-0.49	0.626	-1.71644	1.032303
internet	1.392363	1.848611	0.75	0.451	-2.230848	5.015574
students	1.072526	.558806	1.92	0.055	-.022714	2.167765
_cons	-4.524949	1.658885	-2.73	0.006	-7.776303	-1.273595

```

. test zurich = munich
( 1) [partial]zurich - [partial]munich = 0
      chi2( 1) = 1.03
      Prob > chi2 = 0.3110
.
. esttab reg1 reg2 logit1 logit2, order(crosswise) ///
> compress mtitle nonumber star(+ 0.1 * 0.05 ** 0.01 *** 0.001)

```

	reg1	reg2	logit1	logit2
main				
crosswise		0.172** (2.69)		1.641** (2.82)
zurich	0.130 (0.77)	0.123 (0.96)	0.522 (0.53)	0.757 (1.00)
munich	-0.202 (-1.50)	-0.133 (-1.25)	-1.002 (-1.09)	-0.232 (-0.30)
female	0.0314 (0.27)	0.0409 (0.46)	0.232 (0.29)	0.520 (0.87)
papers3or4	-0.113 (-0.83)	-0.0976 (-0.91)	-0.675 (-0.78)	-0.799 (-1.11)
papers5	0.0880 (0.61)	0.0471 (0.43)	0.223 (0.27)	-0.342 (-0.49)
internet	0.173 (1.02)	0.148 (1.07)	1.012 (0.64)	1.392 (0.75)
students	0.190 (1.38)	0.161 (1.57)	0.955 (1.20)	1.073+ (1.92)
_cons	0.0344	-0.120	-2.303+	-4.525**

	(0.21)	(-0.87)	(-1.78)	(-2.73)
N	306	402	306	402

t statistics in parentheses
+ p<0.1, * p<0.05, ** p<0.01, *** p<0.001

7 Graph: Regression estimates

```
. coefplot reg2 reg1 || logit2 logit1, drop(_cons) xline(0) ///
> bylabels(LPM Logit) byopts(xrescale legend(off))
```

